



RESILIENT | EcoSolid

EcoSolid is an entry level solid tire option available in the 8" to 15" size range.

EcoSolid is designed for use on forklifts in light duty applications.

- ▶ Available only in standard black compound
- ▶ Bead wires to avoid rim slippage
- ▶ Wear indicator built in to lug design

ECOSOLID RANGE

Tire Size	Rim	Width [mm]	Overall Diameter [mm]	Counterbalanced Forklift Truck: load capacity up to 25 km/h		Other Vehicles:	
				Load Wheels [kg]	Steer Wheels [kg]	Load Capacity @ 10 km/h [kg]	Load Capacity @ 25 km/h [kg]
5.00-8	3.00D-8	122	457	1420	1090	1290	1090
15x4½-8	3.00D-8	103	372	1040	800	945	800
16x6-8	4.33R-8	140	409	1495	1150	1360	1150
18x7-8	4.33R-8	145	457	2145	1650	1950	1650
6.00-9	4.00E-9	140	508	1885	1450	1710	1450
21x8-9	6.00E-9	185	508	2755	2120	2500	2120
140/55-9	4.00E-9	127	370	1170	900	1060	900
6.50-10	5.00F-10	163	559	2340	1800	2125	1800
200/50-10	6.50F-10	186	447	2470	1900	2240	1900
23x9-10	6.50F-10	190	571	3445	2650	3125	2650
7.00-12	5.00S-12	168	660	2920	2240	2645	2240
23x10-12	8.00G-12	224	571	3770	2900	3420	2900
27x10-12	8.00G-12	230	656	3900	3000	3540	3000
250-15	7.0-15	216	711	4745	3650	4310	3650
300-15	8.0-15	254	810	5850	4500	5310	4500
28x9-15 (8.15-15)	7.0-15	204	686	3445	2650	3125	2650
8.25-15	6.50-15	206	787	4750	3650	4300	3650
355/65-15	9.75-15	279	808	7800	6000	6430	5450

*In accordance to ETRTO Standard